NSN 4820-01-466-3163

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-466-3163

Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Disk
Disk Loading Method:
Spring
Connection Style:
Flareless all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
16 all ends
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.750 inches all ends
Seat Angle:
12.0 degrees all ends
Product Name:
Valve, 3000 psi hydraulic check, flareless, type ii systems
Material:
Stainless steel
Material Specification:
Astm-a-582, class 304 assn standard single material response
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Style Designator:
Straight thru
Thread Series Designator:
Unjf all ends
Shelf Life:
N/a

NSN 4820-01-466-3163

Check Valve - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0