NSN 4820-01-466-5210

Calibrated Flow Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-466-5210

Body Material:
Brass
Body Style:
Straight thru
Furnished Items:
Union nut and tailpiece
Media For Which Designed:
Water
First End Connection Type:
Unthreaded internal pipe
First End Style Designator:
Socket w/brazing ring
First End Pipe Size Accommodated:
0.500 inches
Second End Relationship With First End:
Identical
Seat Material:
Brass
Flow Control Device:
Diaphragm
Flow Control Device Material:
Rubber, synthetic
End Connection Quantity:
2
Valve Discharge Flow Rate:
0.5 gallons per minute
Regulation Type:
Automatic single stage
Maximum Inlet Pressure Rating:
150.0 pounds per square inch
End Application:
Los angeles class (688)
Special Features:
4manufacturers suggested name is multi-mesurf control automatic balancing valve w/union ends for socket weld 70/30 copper nickel
tailpiece; repair kit is p/n 5471-1sk; maximum operating temp 160 degrees feh; hydrostatic test pressure 450 psi; wt 213 lbs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A21100