NSN 4820-01-466-6320

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-466-6320

Pipe Size Accommodated:
0.500 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Maximum Operating Temp:
425.0 degrees fahrenheit single response
End Application:
Tarawa class lha
Connection Style:
Socket with brazing ring err-100
Valve Operation Method:
Automatic or manual
Connection Type:
Unthreaded internal pipe all ends
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+75.0/+110.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Special Features:
Manufacturers suggested name is bronze relief valve with union end connections for liquid, air/gas service
Material:
Steel comp 316 stem
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Specification Data:
81349-mil-v-24332 government specification
Shelf Life:
A1/-

N/a

NSN 4820-01-466-6320

Safety Relief Valve - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A046b0