## NSN 4820-01-468-4817

Check Valve - Page 1 of 2

Thread Class: 3a all ends

**Thread Direction:** 



View Online at https://aerobasegroup.com/nsn/4820-01-468-4817

Right-hand all ends
Flow Control Device:
Poppet
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Minimum Operating Temp:
-40.0 degrees fahrenheit
End Application:
W/s code usns stalwart class tagos
Connection Style:
Flared (tube) all ends
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
12 all ends
<b>Maximum Operating Pressure:</b>
5000.0 pounds per square inch single response
Thread Size:
1.3125 inches all ends
Seat Angle:
37.0 degrees all ends
Opening Pressure Setting:
6.0 pounds per square inch
Special Features:
Nha crane assembly., mu
Material:
Steel comp 303 body
Media For Which Designed:
Oil, hydraulic single response
Style Designator:
Straight thru
Thread Series Designator:
Unj all ends
Shelf Life:
N/a
Unit Of Measure:

## NSN 4820-01-468-4817

Check Valve - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A530b0