## NSN 4820-01-468-7998

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-468-7998 **Thread Class:** 2a 2nd end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Bonnet Type:** Inside spring **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **Maximum Operating Temp:** 225.0 degrees fahrenheit single response **Minimum Operating Temp:** -20.0 degrees fahrenheit **End Application:** Whidbey island class Isd **Connection Style:** G46b plain (pipe) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded external pipe 2nd end Thready Qty Per Inch (tpi): 12 2nd end **Maximum Operating Pressure:** 6000.0 pounds per square inch single response **Thread Size:** 2.3125 inches 1st end **Opening Pressure Setting:** 80.0 pounds per square inch **Special Features:** Orifice size 0.313 inch Material: Stainless steel seat Media For Which Designed: Air single response **Style Designator:** Err-090

Un 2nd end

**Thread Series Designator:** 

## NSN 4820-01-468-7998

Safety Relief Valve - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0