

View Online at <https://aerobasegroup.com/nsn/4820-01-469-3421>

Pipe Size Accommodated:

2.500 inches all ends

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Connection Style:

G72b beveled (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Butt weld pipe all ends

Maximum Operating Pressure:

150.0 pounds per square inch single response

Product Name:

150 lb class 2 1/2" bolted bonnet globe valve assembly

Special Features:

Ktrim material: disk & seat/stellite 6, stem ss316; only oil free packings and gaskets to be utilized; handwheel=7" dia; mfg suggests using part number, certification data sheet, and drawing number when ordering

Material:

Stainless steel body

Material Specification:

Mil-p-24583, type 1, cl 2, gr 1 military specification 1st material response packing and mil-p-24503, type 2, cl 2, gr 1 military specification 1st material response packing

Media For Which Designed:

Steam single response

Style Designator:

Err-090

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-p-24583 spec.