## NSN 4820-01-469-5447



Check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-01-469-5447 Flow Control Device: Disk **Bolt Hole Quantity:** 12 all ends **End Application:** Arleigh burke class ddg **Valve Operation Method:** Automatic Flange Shape: Round with holes all ends **Connection Type:** Flange all ends **Mounting Position:** Horizontal **Outside Diameter:** 12.500 inches all ends **Bolt Hole Diameter:** 0.880 inches all ends **Bolt Circle Diameter:** 10.620 inches all ends Flange Face Design: Raised with curve and radius all ends **Raised Face Height:** 0.0625 inches all ends **Product Name:** 6 in. Bolted bonnet swing check valve **Special Features:** Asme class 300 lb; system application is for various service; seat diameter is 6 in. Wedge/disc seating surface trim is cf8m or ss316, seat surface trim is stellite 6; 1aw mil-v-18436e Material: Steel uns j92710 flow control device **Material Specification:** Astm a351 cf8c assn standard single material response flow control device **Style Designator:** Straight thru **Furnished Items And Quantity:** 1 gasket Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 4820-01-469-5447

Check Valve - Page 2 of 2



Fiig:

A530b0