## NSN 4820-01-469-8863

Check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-469-8863

O.500 inches all ends Flow Control Device: Disk End Application: Arleigh burke class ddg Connection Style: Reduced socket (pipe) all ends Valve Operation Method: Manual Connection Type: Unthreaded internal pipe all ends Mounting Position: Vertical Valve Size: O.500 inches First Connection Face To Centerline Distance: 2.000 inches Second Connection Face To Centerline Distance: 2.000 inches Material: Copper alloy body Style Designator: Angle flanged ends Shelf Life:
Disk  End Application:  Arleigh burke class ddg  Connection Style:  Reduced socket (pipe) all ends  Valve Operation Method:  Manual  Connection Type:  Unthreaded internal pipe all ends  Mounting Position:  Vertical  Valve Size:  0.500 inches  First Connection Face To Centerline Distance:  2.000 inches  Second Connection Face To Centerline Distance:  2.000 inches  Material:  Copper alloy body  Style Designator:  Angle flanged ends  Shelf Life:
End Application: Arleigh burke class ddg Connection Style: Reduced socket (pipe) all ends Valve Operation Method: Manual Connection Type: Unthreaded internal pipe all ends Mounting Position: Vertical Valve Size: 0.500 inches First Connection Face To Centerline Distance: 2.000 inches Second Connection Face To Centerline Distance: 2.000 inches Material: Copper alloy body Style Designator: Angle flanged ends Shelf Life:
Arleigh burke class ddg  Connection Style: Reduced socket (pipe) all ends  Valve Operation Method: Manual  Connection Type: Unthreaded internal pipe all ends  Mounting Position: Vertical  Valve Size: 0.500 inches  First Connection Face To Centerline Distance: 2.000 inches  Second Connection Face To Centerline Distance: 2.000 inches  Material: Copper alloy body  Style Designator: Angle flanged ends  Shelf Life:
Connection Style: Reduced socket (pipe) all ends Valve Operation Method: Manual Connection Type: Unthreaded internal pipe all ends Mounting Position: Vertical Valve Size: 0.500 inches First Connection Face To Centerline Distance: 2.000 inches Second Connection Face To Centerline Distance: 2.000 inches Material: Copper alloy body Style Designator: Angle flanged ends Shelf Life:
Reduced socket (pipe) all ends  Valve Operation Method:  Manual  Connection Type: Unthreaded internal pipe all ends  Mounting Position:  Vertical  Valve Size: 0.500 inches  First Connection Face To Centerline Distance: 2.000 inches  Second Connection Face To Centerline Distance: 2.000 inches  Material:  Copper alloy body  Style Designator:  Angle flanged ends  Shelf Life:
Valve Operation Method:  Manual  Connection Type: Unthreaded internal pipe all ends  Mounting Position:  Vertical  Valve Size: 0.500 inches  First Connection Face To Centerline Distance: 2.000 inches  Second Connection Face To Centerline Distance: 2.000 inches  Material:  Copper alloy body  Style Designator:  Angle flanged ends  Shelf Life:
Manual  Connection Type: Unthreaded internal pipe all ends  Mounting Position: Vertical  Valve Size: 0.500 inches  First Connection Face To Centerline Distance: 2.000 inches  Second Connection Face To Centerline Distance: 2.000 inches  Material: Copper alloy body  Style Designator: Angle flanged ends  Shelf Life:
Connection Type: Unthreaded internal pipe all ends Mounting Position: Vertical Valve Size: 0.500 inches First Connection Face To Centerline Distance: 2.000 inches Second Connection Face To Centerline Distance: 2.000 inches Material: Copper alloy body Style Designator: Angle flanged ends Shelf Life:
Unthreaded internal pipe all ends  Mounting Position:  Vertical  Valve Size:  0.500 inches  First Connection Face To Centerline Distance:  2.000 inches  Second Connection Face To Centerline Distance:  2.000 inches  Material:  Copper alloy body  Style Designator:  Angle flanged ends  Shelf Life:
Mounting Position:  Vertical  Valve Size:  0.500 inches  First Connection Face To Centerline Distance:  2.000 inches  Second Connection Face To Centerline Distance:  2.000 inches  Material:  Copper alloy body  Style Designator:  Angle flanged ends  Shelf Life:
Vertical  Valve Size: 0.500 inches  First Connection Face To Centerline Distance: 2.000 inches  Second Connection Face To Centerline Distance: 2.000 inches  Material:  Copper alloy body  Style Designator:  Angle flanged ends  Shelf Life:
Valve Size:  0.500 inches  First Connection Face To Centerline Distance:  2.000 inches  Second Connection Face To Centerline Distance:  2.000 inches  Material:  Copper alloy body  Style Designator:  Angle flanged ends  Shelf Life:
0.500 inches  First Connection Face To Centerline Distance: 2.000 inches  Second Connection Face To Centerline Distance: 2.000 inches  Material:  Copper alloy body  Style Designator:  Angle flanged ends  Shelf Life:
First Connection Face To Centerline Distance:  2.000 inches  Second Connection Face To Centerline Distance:  2.000 inches  Material:  Copper alloy body  Style Designator:  Angle flanged ends  Shelf Life:
2.000 inches  Second Connection Face To Centerline Distance: 2.000 inches  Material:  Copper alloy body  Style Designator:  Angle flanged ends  Shelf Life:
Second Connection Face To Centerline Distance: 2.000 inches  Material: Copper alloy body Style Designator: Angle flanged ends Shelf Life:
2.000 inches  Material: Copper alloy body Style Designator: Angle flanged ends Shelf Life:
Material: Copper alloy body Style Designator: Angle flanged ends Shelf Life:
Copper alloy body Style Designator: Angle flanged ends Shelf Life:
Style Designator: Angle flanged ends Shelf Life:
Angle flanged ends Shelf Life:
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A530b0