NSN 4820-01-470-7729

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-470-7729

| Flow Control Device: |
|--|
| Poppet |
| Valve Discharge Flow Rate: |
| 26.0 liters per minute |
| Maximum Operating Temp: |
| 135.0 degrees celsius single response |
| Connection Style: |
| Reduced socket (tube) err-100 |
| Length: |
| 34.40 millimeters all ends |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Unthreaded cartridge all ends |
| Maximum Operating Pressure: |
| 4.0 bar single response |
| Opening Pressure Setting: |
| 7.5 bar |
| Outside Diameter: |
| 23.47 millimeters all ends |
| Material: |
| Aluminum alloy 2024 body |
| Material Specification: |
| Qq-a-225/6 federal specification single material response body |
| Media For Which Designed: |
| Hydraulic fluid, petroleum base single response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625, ty1 military specification single treatment response |
| Style Designator: |
| Err-090 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A046b0 |
| Mil-std (military Standard): |

Mil-a-8625 spec.