Directional Control Linear Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-471-6619

6 Valve Operation Method: Solenoid Connection Type: Threaded external pipe Maximum Operating Pressure And Media For Which Designed: 3000.0 pounds per square inch fuel/oil, hydrocarbon Thread Size: 0.375 inches and 0.250 inches Body Material: Steel Maximum Operating Tempurature And Media For Which Designed:
Solenoid Connection Type: Threaded external pipe Maximum Operating Pressure And Media For Which Designed: 3000.0 pounds per square inch fuel/oil, hydrocarbon Thread Size: 0.375 inches and 0.250 inches Body Material: Steel
Connection Type: Threaded external pipe Maximum Operating Pressure And Media For Which Designed: 3000.0 pounds per square inch fuel/oil, hydrocarbon Thread Size: 0.375 inches and 0.250 inches Body Material: Steel
Threaded external pipe Maximum Operating Pressure And Media For Which Designed: 3000.0 pounds per square inch fuel/oil, hydrocarbon Thread Size: 0.375 inches and 0.250 inches Body Material: Steel
Maximum Operating Pressure And Media For Which Designed: 3000.0 pounds per square inch fuel/oil, hydrocarbon Thread Size: 0.375 inches and 0.250 inches Body Material: Steel
3000.0 pounds per square inch fuel/oil, hydrocarbon Thread Size: 0.375 inches and 0.250 inches Body Material: Steel
Thread Size: 0.375 inches and 0.250 inches Body Material: Steel
0.375 inches and 0.250 inches Body Material: Steel
Body Material: Steel
Steel
Maximum Operating Tempurature And Media For Which Designed:
200.0 degrees fahrenheit fuel/oil, hydrocarbon
Special Features:
Divider valve; lubricant oil or grease; zinc plated; delivers metered amount of lubricant
Thread Series Designator:
Nptf
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A506h0