## NSN 4820-01-474-7838

Safety Relief Valve - Page 1 of 1

Fiig: A046b0



View Online at https://aerobasegroup.com/nsn/4820-01-474-7838

Valve Operation Method:
Automatic
Maximum Operating Pressure:
182.0 pounds per square inch single response
Outside Diameter Tube Accommodated:
1.000 inches all ends
Special Features:
Next higher assembly nsn 5999-01-411-7098, cooler, fluid, electronic equipment. 82 plus/minus psi.Suppgitem used in a high purity cooling
system. St be thoroughly cleaned and free from grease, oil, fluxes, liquid contaminants of any kind and other foreign material such as metal
chips or lint. All ports and connections shall be sealed and protected with caps, plugs and any means suitable in prohibiting the entrance of
foreign material during shipping and storage. Agavgnsn 1430-01-418-4396, radar set, semitrailer mounted
Material:
Stainless steel
Material Specification:
Astm a582, 300 series assn standard single material response or ams 5640, 300 series assn standard single material response or
ams5641, 300 series assn standard single material response
Media For Which Designed:
Ethylene glycol 1st response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No