NSN 4820-01-474-8728



Check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-01-474-8728 **Thread Direction:** Right-hand all ends **Flow Control Device: Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 212.0 degrees fahrenheit single response **Minimum Operating Temp:** -20.0 degrees fahrenheit **End Application:** Nsn 4930-01-388-9490 hydrant refueling system, air transportable; f-16 aircraft **Connection Style:** Plain, optional end (pipe) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal pipe all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 1500.0 pounds per square inch single response **Thread Size:** 0.500 inches all ends **Opening Pressure Setting:** 1.0 pounds per square inch **Special Features:** For hydraulic and pneumatic systems Material: Copper alloy 360 body **Material Specification:** Astm b16 assn standard single material response body **Style Designator:** Straight thru **Thread Series Designator:** Npt all ends Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 4820-01-474-8728

Check Valve - Page 2 of 2



Fiig:

A530b0