NSN 4820-01-481-2270

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-481-2270
Pipe Size Accommodated:
0.375 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Connection Style:
Socket with brazing ring err-100
Valve Operation Method:
Automatic
Connection Type:
Unthreaded internal pipe all ends
Adjustable Pressure Range:
+5.0/+9.0 pounds per square inch
Product Name:
Relief valve, type 1551-t.
Special Features:
This valve is approximately 10 inches in height and requires an additional 2 inches clearance for disassembly. Approved as class "a" by
buships nnva, jan 30, 1970. Drawing was originally from kunkle valve (cage 34494) which was purchased by anderson greenwood (cage
01343).
Material:
Nickel alloy flow control device
Material Specification:
Qq-n-281 federal specification single material response stem
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Furnished Items And Quantity:
2 brazing ring and 2 tailpiece and 1 wrench
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

A046b0

Fiig: