

View Online at <https://aerobasegroup.com/nsn/4820-01-481-2270>

Pipe Size Accommodated:

0.375 inches all ends

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Connection Style:

Socket with brazing ring err-100

Valve Operation Method:

Automatic

Connection Type:

Unthreaded internal pipe all ends

Adjustable Pressure Range:

+5.0/+9.0 pounds per square inch

Product Name:

Relief valve, type 1551-t.

Special Features:

This valve is approximately 10 inches in height and requires an additional 2 inches clearance for disassembly. Approved as class "a" by buships nnva, jan 30, 1970. Drawing was originally from kunkle valve (cage 34494) which was purchased by anderson greenwood (cage 01343).

Material:

Nickel alloy flow control device

Material Specification:

Qq-n-281 federal specification single material response stem

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Furnished Items And Quantity:

2 brazing ring and 2 tailpiece and 1 wrench

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0