

View Online at <https://aerobasegroup.com/nsn/4820-01-481-2587>

Body Material:

Copper alloy

Body Style:

Straight thru

Stem Material:

Nickel-copper alloy, qq-n-281, class b

Furnished Items:

Brazing ring

Media For Which Designed:

Water, salt

First End Connection Type:

Unthreaded internal pipe

First End Style Designator:

Socket w/brazing ring

First End Pipe Size Accommodated:

0.750 inches

Second End Relationship With First End:

Identical

Seat Material:

Nickel copper alloy

Flow Control Device:

Disk

Flow Control Device Material:

Rubber, buna-n

End Connection Quantity:

2

Renewable Seat Ring Type:

Threaded

Outlet Pressure Range:

+50.0/+150.0 pounds per square inch

Regulation Type:

Automatic single stage

Valve Loading Method:

Spring

Filter:

Not included

End Application:

W/s designator tarawa class lha

Tempurature Rating:

165.0 degrees fahrenheit

Product Name:

Sea water pressure reducing valve.

Special Features:

When ordering this valve you must specify the following items if you want to receive them with the valve: tool, seat ring, p/n 40398-4, find no. 30; and tailpieces, 40398-4, find no. 12, and union nuts, 40398-4, find no. 10

Special Test Features:

Hi shock testing and vibration testing, aero nav laboratories, 9-4042, 12/29/99.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A21100