NSN 4820-01-481-4583

Globe Valve - Page 1 of 2

Pipe Size Accommodated:

1.000 inches all ends
Flow Control Device:

N/a

Unit Of Measure:



View Online at https://aerobasegroup.com/nsn/4820-01-481-4583

Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Union
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Connection Style:
Socket with brazing ring all ends
Valve Operation Method:
Manual
Connection Type:
Unthreaded internal pipe all ends
Maximum Operating Pressure:
400.0 pounds per square inch single response
Product Name:
1.00" bronze union end globe stop valve
Special Features:
Assembly -51a (mod) is modified from dwg by virgin polytetrafluoroethylene material for packing & o-rings; by silver-braze, union tailpieces
and union nuts, iaw dwg 53711 7063850. This valve is for tank level indicator system service. Similar to 4820-01-481-4847 which has viton
o-rings and socket weld tailpieces.
Material:
Nickel alloy flow control device
Material Specification:
Qq-n-281 federal specification single material response stem
Media For Which Designed:
Liquid single response
Style Designator:
A1 straight thru
Test Data Document:
Supship n.N. Va letter 9505 ser cvn68rcoh-261-b/1397, dated june 15, 1998 specification (includes engineering type bulletins, brochures,
etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade
publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as
"typical", "average", "", etc.).
Furnished Items And Quantity:
2 brazing ring and 1 handwheel and 2 tailpiece and 2 nut
Shelf Life:

NSN 4820-01-481-4583

Globe Valve - Page 2 of 2



Fiig:

A046b0