NSN 4820-01-482-2538

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:

Bonnet Attachment Method:

1.500 inches all ends

Flow Control Device:

Stem

Bonnet Type: Inside spring



View Online at https://aerobasegroup.com/nsn/4820-01-482-2538

Bolted
Disk Loading Method:
Spring
Maximum Operating Temp:
425.0 degrees fahrenheit 2nd response
End Application:
W/s designator tawara class lha
Connection Style:
Socket with brazing ring err-100
Valve Operation Method:
Automatic
Connection Type:
Unthreaded internal pipe all ends
Features Provided:
Bonnet packing
Adjustable Pressure Range:
+8.0/+10.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch 1st response
Opening Pressure Setting:
9.00 pounds per square inch
Material:
Stainless steel stem
Material Specification:
Astm b61 assn standard single material response body
Media For Which Designed:
Gas, inert 2nd response
Style Designator:
Err-090
Furnished Items And Quantity:
2 brazing ring and 1 lever and 2 tailpiece and 2 nut
Shelf Life:
N/a
Unit Of Measure:

NSN 4820-01-482-2538

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0