

View Online at <https://aerobasegroup.com/nsn/4820-01-484-3459>

Pipe Size Accommodated:

0.625 inches all ends

Renewable Seat Ring Type:

Pressed-in

Connection Style:

Reduced socket one brazing ring (tube) all ends

Valve Operation Method:

Manual

Connection Type:

Unthreaded internal pipe all ends

Special Features:

This valve is designed for (unspecified) refrigerant, (unspecified) water, and (unspecified) oil. Tested and approved for refrigerant. Tested and approved for hi-shock and vibration.

Material:

Stainless steel stem

Material Specification:

Astm b283-ca377 assn standard single material response body

Media For Which Designed:

Liquid single response

Style Designator:

Err-090

Test Data Document:

Navsea letter 9516, opr: 56y15, ser 56y152/238 may 23, 1991 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And mil-std-901c gr a, class 1, type a and military std-1578 type 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0