## NSN 4820-01-487-3165

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-487-3165

Pipe Size Accommodated:
0.500 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
350.0 degrees fahrenheit single response
End Application:
Cvn-68
Connection Style:
Plain (tube) err-100
Valve Operation Method:
Automatic
Connection Type:
Flange all ends
Adjustable Pressure Range:
+121.0/+135.0 pounds per square inch
Maximum Operating Pressure:
135.0 pounds per square inch single response
Opening Pressure Setting:
135.0 pounds per square inch
Product Name:
1/2 inch relief valve, type 2741s
Special Features:
Service usage: main feed, cvn-68 overhaul
Material:
Steel uns j92600 body
Material Specification:
Astm a479 type 304 assn standard single material response flow control device
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-01-487-3165

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0