NSN 4820-01-488-4539

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-488-4539

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Maximum Operating Temp:
165.0 degrees fahrenheit single response
End Application:
Los angeles class ssn (688)
Valve Operation Method:
Automatic
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Maximum Operating Pressure:
125.0 pounds per square inch single response
Opening Pressure Setting:
110.0 pounds per square inch
First Connection Face To Centerline Distance:
4.000 inches
Second Connection Face To Centerline Distance:
4.250 inches
Product Name:
1-1/2" relief valve, type uu 1571-t
Special Features:
Pressure range is 109 to 125 psig
Material:
Nickel alloy flow control device
Material Specification:
Qq-n-288 comp a assn standard single material response seat
Media For Which Designed:
Air single response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-01-488-4539

Safety Relief Valve - Page 2 of 2



Demi			

Yes - demil/mli

Fiig:

A046b0

Mil-std (military Standard):

Mil-v-22549 spec.