# NSN 4820-01-488-4539

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-488-4539



# Flow Control Device:

Disk

Bonnet Type:

Inside spring

# **Bonnet Attachment Method:**

Bolted

#### **Disk Loading Method:**

Spring

#### Maximum Operating Temp:

165.0 degrees fahrenheit single response

#### **End Application:**

Los angeles class ssn (688)

#### Valve Operation Method:

Automatic

#### **Connection Type:**

Flange all ends

#### Valve Size:

1.500 inches

# Maximum Operating Pressure:

125.0 pounds per square inch single response

# **Opening Pressure Setting:**

110.0 pounds per square inch

# First Connection Face To Centerline Distance:

4.000 inches

# Second Connection Face To Centerline Distance:

4.250 inches

# Product Name:

1-1/2" relief valve, type uu 1571-t

# **Special Features:**

Pressure range is 109 to 125 psig

# Material:

Nickel alloy flow control device

#### Material Specification:

Qq-n-288 comp a assn standard single material response seat

#### Media For Which Designed:

Air single response

#### Style Designator:

Err-090

#### Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 4820-01-488-4539

Safety Relief Valve - Page 2 of 2



# Demilitarization:

Yes - demil/mli

Fiig:

A046b0

# Mil-std (military Standard):

Mil-v-22549 spec.