## NSN 4820-01-489-1135

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:



View Online at https://aerobasegroup.com/nsn/4820-01-489-1135

0.750 inches all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
<b>Bonnet Attachment Method:</b>
Integral
Disk Loading Method:
Spring
End Application:
Filter separator
Connection Style:
G9 plain, optional en (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 2nd end
Thready Qty Per Inch (tpi):
14 all ends
Adjustable Pressure Range:
+115.0/+250.0 pounds per square inch
Thread Size:
0.750 inches all ends
Seat Angle:
45.0 degrees 1st end
Opening Pressure Setting:
200.0 pounds per square inch
Special Features:
Service application hydraulic or pneumatic
Material:
Stainless steel flow control device
Surface Treatment:
Anodize
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-01-489-1135

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0