## NSN 4820-01-491-6878

Calibrated Flow Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-491-6878

| Body Material:  |
|---|
| Any acceptable  |
| Body Style:   |
| Straight thru   |
| Media For Which Designed:                                       |
| Hydraulic fluid, mil-h-5606 and hydraulic fluid, petroleum base |
| First End Connection Type:                                      |
| Threaded internal boss  |
| First End Style Designator:                                     |
| Gasket seal   |
| First End Thread Size And Series/type Designator:               |
| 3/4-16 unf  |
| First End Thread Class:   |
| 3b  |
| First End Thread Direction:                                     |
| Right-hand  |
| Second End Relationship With First End:                         |
| Identical   |
| Flow Control Device:  |
| Piston, spring loaded   |
| End Connection Quantity:  |
| 2   |
| Valve Discharge Flow Rate:                                      |
| 5.0 gallons per minute  |
| Maximum Inlet Pressure Rating:                                  |
| 3000.0 pounds per square inch                                   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A21100  |
|   |
|   |