

View Online at <https://aerobasegroup.com/nsn/4820-01-492-3560>

**Body Material:**

Brass

**Body Style:**

Straight thru

**Media For Which Designed:**

Air and helium and hydrogen and hydraulic fluid, mil-h-5606 and natural gas and water and lube oil and hydraulic fluid (mineral base) and ammonia and alcohol and nitrogen

**First End Connection Type:**

Threaded internal pipe

**First End Pipe Size Accommodated:**

0.250 inches

**Second End Relationship With First End:**

Identical

**Flow Control Device:**

Poppet

**End Connection Quantity:**

2

**Renewable Seat Ring Type:**

Pressed-in

**Regulation Type:**

Automatic single stage

**Valve Loading Method:**

Bellows and spring

**Maximum Inlet Pressure Rating:**

3000.0 pounds per square inch

**Outlet Pressure Setting:**

60.0 pounds per square inch

**Outlet Pressure Accuracy Rating:**

1.000 pounds per square inch

**End Application:**

Aircraft, b-2 bomber (atb)

**Tempurature Rating:**

Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Product Name:**

Pressure blanking valve (gauge saver)

**Special Features:**

O-ring material is buna-n iaw mil-p-25732

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A21100