

View Online at <https://aerobasegroup.com/nsn/4820-01-492-3560>

Body Material:

Brass

Body Style:

Straight thru

Media For Which Designed:

Air and helium and hydrogen and hydraulic fluid, mil-h-5606 and natural gas and water and lube oil and hydraulic fluid (mineral base) and ammonia and alcohol and nitrogen

First End Connection Type:

Threaded internal pipe

First End Pipe Size Accommodated:

0.250 inches

Second End Relationship With First End:

Identical

Flow Control Device:

Poppet

End Connection Quantity:

2

Renewable Seat Ring Type:

Pressed-in

Regulation Type:

Automatic single stage

Valve Loading Method:

Bellows and spring

Maximum Inlet Pressure Rating:

3000.0 pounds per square inch

Outlet Pressure Setting:

60.0 pounds per square inch

Outlet Pressure Accuracy Rating:

1.000 pounds per square inch

End Application:

Aircraft, b-2 bomber (atb)

Tempurature Rating:

Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit

Product Name:

Pressure blanking valve (gauge saver)

Special Features:

O-ring material is buna-n iaw mil-p-25732

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A21100