## NSN 4820-01-492-4455

Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-492-4455

**Body Material:** 

Steel, federal standard 66, aisi 316/sae 30316

**Body Style:** 

Straight thru

Stem Material:

Steel, qq-s-764, type 416-canceled

Media For Which Designed:

Water, oil or gas

**First End Connection Type:** 

Threaded internal tube

First End Style Designator:

Gasket seal

First End Outside Diameter Tube Accommodated:

0.250 inches

First End Thread Size And Series/type Designator:

L1/4-18 unf

**First End Thread Class:** 

2b

First End Thread Direction:

Right-hand

**Second End Relationship With First End:** 

Identical

**Seat Material:** 

Steel, qq-s-764, type 416-canceled

**Face To Face Distance:** 

5.060 inches

Flow Control Device:

Plua

Flow Control Device Material:

Steel, qq-s-764, type 416-canceled

**End Connection Quantity:** 

2

**Outlet Pressure Range:** 

+13.0/+30.0 pounds per square inch

Regulation Type:

Automatic single stage

Valve Loading Method:

Spring

**Remote Actuation Method:** 

Diaphragm

**Maximum Inlet Pressure Rating:** 

300.0 pounds per square inch

## NSN 4820-01-492-4455

Fluid Pressure Regulating Valve - Page 2 of 2



Filter:
Not included
Tempurature Rating:
Between -20.0 degrees fahrenheit and 450.0 degrees fahrenheit
Special Features:
law ms16142 and as 478, boss gasket seal.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A21100