

View Online at <https://aerobasegroup.com/nsn/4820-01-492-4455>

Body Material:

Steel, federal standard 66, aisi 316/sae 30316

Body Style:

Straight thru

Stem Material:

Steel, qq-s-764, type 416-canceled

Media For Which Designed:

Water, oil or gas

First End Connection Type:

Threaded internal tube

First End Style Designator:

Gasket seal

First End Outside Diameter Tube Accommodated:

0.250 inches

First End Thread Size And Series/type Designator:

L1/4-18 unf

First End Thread Class:

2b

First End Thread Direction:

Right-hand

Second End Relationship With First End:

Identical

Seat Material:

Steel, qq-s-764, type 416-canceled

Face To Face Distance:

5.060 inches

Flow Control Device:

Plug

Flow Control Device Material:

Steel, qq-s-764, type 416-canceled

End Connection Quantity:

2

Outlet Pressure Range:

+13.0/+30.0 pounds per square inch

Regulation Type:

Automatic single stage

Valve Loading Method:

Spring

Remote Actuation Method:

Diaphragm

Maximum Inlet Pressure Rating:

300.0 pounds per square inch

Filter:

Not included

Tempurature Rating:

Between -20.0 degrees fahrenheit and 450.0 degrees fahrenheit

Special Features:

law ms16142 and as 478, boss gasket seal.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100