# NSN 4820-01-492-6232

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-492-6232

# Pipe Size Accommodated:

1.000 inches all ends

## **Thread Class:**

2a all ends

### **Thread Direction:**

Right-hand all ends

# Flow Control Device:

Poppet

#### **End Application:**

4810-01-492-5803, butterfly valve assembly.

#### **Connection Style:**

G46b plain (pipe) all ends

#### Valve Operation Method:

Automatic

## Thread Size:

0.875 inches all ends

# **Opening Pressure Setting:**

1000.0 pounds per square inch

#### **Special Features:**

Next higher assembly 4820-01-492-5684, manifold valve assembly. This valve designed for use with general purpose hydraulic fluid iaw mil-h-5606, sae number 10. Seal material is buna-n. Flow rate is 10 gpm. Similar to 4820-01-492-6053 which has flow rate of 20 gpm, both have same nha and end item

# Material:

Steel

# Media For Which Designed:

Fuel/oil, hydrocarbon single response

#### **Style Designator:**

Err-090

### **Thread Series Designator:**

Unf all ends

#### Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A046b0