NSN 4820-01-492-6237

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-492-6237

view offilite at https://defobasegroup.com/hsh/4020-01-432-020/
Pipe Size Accommodated:
1.250 inches all ends
Thread Class:
2a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
End Application:
4810-01-492-5803, butterfly valve assembly.
Connection Style:
Plain (pipe) all ends
Valve Operation Method:
Automatic
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.875 inches all ends
Opening Pressure Setting:
15.0 pounds per square inch
Product Name:
Pilot check valve
Special Features:
Next higher assembly 4820-01-492-5684, manifold valve assembly. This valve designed for use with general purpose hydraulic fluid iaw
mil-h-5606, sae number 10. Seal material is buna-n. Rated flow rate 6.0 gpm
Material:
Steel
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
Screw-in cartridge
Thread Series Designator:
Unf all ends
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

NSN 4820-01-492-6237

Check Valve - Page 2 of 2



Fiig:

A530b0