## NSN 4820-01-494-3092

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-494-3092

Pipe Size Accommodated:
0.750 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Minimum Operating Temp:
-60.0 degrees fahrenheit
Connection Style:
G5b flar (gas fitting) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 2nd end
Thready Qty Per Inch (tpi):
27 1st end
Maximum Operating Pressure:
900.0 pounds per square inch single response
Thread Size:
0.750 inches 2nd end
Opening Pressure Setting:
475.0 pounds per square inch
Special Features:
Nozzle inlet; valve iaw asme section viii.
Material:
Steel comp 316 flow control device
Material Specification:
Astm b564 alloy b4400 assn standard single material response body
Style Designator:
Err-090
Thread Series Designator:
Npt 1st end
Furnished Items And Quantity:

1 lever

## NSN 4820-01-494-3092

Safety Relief Valve - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0