NSN 4820-01-494-3092

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-494-3092

Pipe Size Accommodated:

0.750 inches 2nd end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Maximum Operating Temp:

400.0 degrees fahrenheit single response

Minimum Operating Temp:

-60.0 degrees fahrenheit

Connection Style:

G5b flar (gas fitting) 2nd end

Valve Operation Method:

Automatic

Connection Type:

Threaded internal pipe 2nd end

Thready Qty Per Inch (tpi):

27 1st end

Maximum Operating Pressure:

900.0 pounds per square inch single response

Thread Size:

0.750 inches 2nd end

Opening Pressure Setting:

475.0 pounds per square inch

Special Features:

Nozzle inlet; valve iaw asme section viii.

Material:

Steel comp 316 flow control device

Material Specification:

Astm b564 alloy b4400 assn standard single material response body

Style Designator:

Err-090

Thread Series Designator:

Npt 1st end

Furnished Items And Quantity:

1 lever

NSN 4820-01-494-3092

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

