## **NSN 4820-01-495-3788**Safety Relief Valve - Page 1 of 2



Salety Keller valve - Page 1 01 2
View Online at https://aerobasegroup.com/nsn/4820-01-495-3788
Pipe Size Accommodated:
1.500 inches 2nd end
Flow Control Device:
Disk
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 2nd end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Mounting Facility:
Bracket
Valve Size:
2.500 inches
Adjustable Pressure Range:
+156.0/+183.0 pounds per square inch
Outside Diameter:
5.000 inches 2nd end
Thickness:
0.625 inches 1st end
First Connection Face To Centerline Distance:
3.875 inches
Bolt Hole Diameter:
0.750 inches 1st end
Second Connection Face To Centerline Distance:
3.875 inches
Bolt Circle Diameter:
5.500 inches 1st end

Flange Face Design:

Plain 2nd end

**Product Name:** 

Steel relief valve 1 1/2 x 2 1/2 g oriface

**Special Features:** 

Flange faces plain w/raised faces, approx 1/16in

Material:

Stainless steel stem

## NSN 4820-01-495-3788

Safety Relief Valve - Page 2 of 2



<b>Material</b>	<b>Specific</b>	ation:

Astm-a-276-gr-304 assn standard single material response flow control device

**Style Designator:** 

Err-090

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0