NSN 4820-01-498-3537

Poppet Drain Cock - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-498-3537

| Flow Control Device: |
|--|
| Poppet |
| Maximum Operating Temp: |
| 160.0 degrees fahrenheit single response |
| Minimum Operating Temp: |
| -65.0 degrees fahrenheit |
| Valve Operation Method: |
| Manual |
| Maximum Operating Pressure: |
| 60.0 pounds per square inch single response |
| Special Features: |
| Spring material: cres 302, will not lock in open position, torque value installation in 14-16 ft.Lbs.Agavge/i: fuel system to apache longbow |
| helicopter. |
| Material: |
| Aluminum alloy 2024 body |
| Material Specification: |
| Ams qq-s-225/6 assn standard single material response body |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Surface Treatment Specification: |
| Mil-c-5541, class 3 military specification single treatment response |
| Style Designator: |
| Straight thru |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A530c0 |
| Mil-std (military Standard): |
| Mil-c-5541 spec. |
| |
| |
| |