NSN 4820-01-499-5885

Body Material:

Body Style:

Steel, corrosion resisting

Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-499-5885

Straight thru
First End Connection Type:
Threaded internal pipe
First End Style Designator:
Plain
First End Thread Size And Series/type Designator:
3/8-18 npt
First End Thread Direction:
Right-hand
Second End Relationship With First End:
Identical
Seat Material:
Plastic, polychlorotrifluoroethylene
Packing Material:
Rubber, buna-n
Flow Control Device:
Diaphragm
Flow Control Device Material:
Rubber, buna-n
End Connection Quantity:
2
2 Mounting Facility:
Mounting Facility:
Mounting Facility: Panel
Mounting Facility: Panel Outlet Pressure Range:
Mounting Facility: Panel Outlet Pressure Range: +2.0/+150.0 pounds per square inch
Mounting Facility: Panel Outlet Pressure Range: +2.0/+150.0 pounds per square inch Regulation Type:
Mounting Facility: Panel Outlet Pressure Range: +2.0/+150.0 pounds per square inch Regulation Type: Automatic single stage
Mounting Facility: Panel Outlet Pressure Range: +2.0/+150.0 pounds per square inch Regulation Type: Automatic single stage Manual Control Method:
Mounting Facility: Panel Outlet Pressure Range: +2.0/+150.0 pounds per square inch Regulation Type: Automatic single stage Manual Control Method: Knob
Mounting Facility: Panel Outlet Pressure Range: +2.0/+150.0 pounds per square inch Regulation Type: Automatic single stage Manual Control Method: Knob Valve Loading Method:
Mounting Facility: Panel Outlet Pressure Range: +2.0/+150.0 pounds per square inch Regulation Type: Automatic single stage Manual Control Method: Knob Valve Loading Method: Spring
Mounting Facility: Panel Outlet Pressure Range: +2.0/+150.0 pounds per square inch Regulation Type: Automatic single stage Manual Control Method: Knob Valve Loading Method: Spring Maximum Inlet Pressure Rating:
Mounting Facility: Panel Outlet Pressure Range: +2.0/+150.0 pounds per square inch Regulation Type: Automatic single stage Manual Control Method: Knob Valve Loading Method: Spring Maximum Inlet Pressure Rating: 6000.0 pounds per square inch
Mounting Facility: Panel Outlet Pressure Range: +2.0/+150.0 pounds per square inch Regulation Type: Automatic single stage Manual Control Method: Knob Valve Loading Method: Spring Maximum Inlet Pressure Rating: 6000.0 pounds per square inch Filter:
Mounting Facility: Panel Outlet Pressure Range: +2.0/+150.0 pounds per square inch Regulation Type: Automatic single stage Manual Control Method: Knob Valve Loading Method: Spring Maximum Inlet Pressure Rating: 6000.0 pounds per square inch Filter: Included
Mounting Facility: Panel Outlet Pressure Range: +2.0/+150.0 pounds per square inch Regulation Type: Automatic single stage Manual Control Method: Knob Valve Loading Method: Spring Maximum Inlet Pressure Rating: 6000.0 pounds per square inch Filter: Included Tempurature Rating:
Mounting Facility: Panel Outlet Pressure Range: +2.0/+150.0 pounds per square inch Regulation Type: Automatic single stage Manual Control Method: Knob Valve Loading Method: Spring Maximum Inlet Pressure Rating: 6000.0 pounds per square inch Filter: Included Tempurature Rating: Between -55.0 degrees celsius and 74.0 degrees celsius

NSN 4820-01-499-5885

Fluid Pressure Regulating Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A21100