

View Online at <https://aerobasegroup.com/nsn/4820-01-502-1447>

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Bolt Hole Quantity:

8 all ends

Maximum Operating Temp:

425.0 degrees fahrenheit single response

Valve Operation Method:

Automatic or manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Facility:

Bracket

Valve Size:

4.000 inches

Adjustable Pressure Range:

+71.0/+100.0 pounds per square inch

Maximum Operating Pressure:

100.0 pounds per square inch single response

Opening Pressure Setting:

71.0 pounds per square inch

Outside Diameter:

7.6875 inches all ends

Thickness:

0.500 inches all ends

First Connection Face To Centerline Distance:

7.000 inches

Bolt Hole Diameter:

0.5625 inches all ends

Second Connection Face To Centerline Distance:

6.000 inches

Bolt Circle Diameter:

6.5625 inches all ends

Flange Face Design:

Plain all ends

Product Name:

4 x 4 modle I-2210-c relief valve

Material:

Nickel alloy flow control device

Material Specification:

Qq-n-288 assn standard single material response flow control device

Media For Which Designed:

Water, salt single response

Style Designator:

Err-090

Specification Data:

81349-mil-v-20065 type a-1 class c government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-b-16541 spec.