## NSN 4820-01-502-9839

Check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-502-9839

Flow Control Device:
Poppet
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Minimum Operating Temp:
-65.0 degrees fahrenheit
End Application:
Aircraft, c-5 galaxy
Connection Style:
Flareless 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 2nd end
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Special Features:
Cracking pressure 2 to 8 psi
Material:
Aluminum alloy 2024 body
Aluminum alloy 2024 body  Media For Which Designed:
Media For Which Designed:
Media For Which Designed:  Hydraulic fluid, petroleum base single response
Media For Which Designed: Hydraulic fluid, petroleum base single response Surface Treatment:
Media For Which Designed: Hydraulic fluid, petroleum base single response Surface Treatment: Anodize
Media For Which Designed: Hydraulic fluid, petroleum base single response Surface Treatment: Anodize Surface Treatment Specification:
Media For Which Designed: Hydraulic fluid, petroleum base single response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 type 1 military specification single treatment response
Media For Which Designed: Hydraulic fluid, petroleum base single response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 type 1 military specification single treatment response Style Designator:
Media For Which Designed: Hydraulic fluid, petroleum base single response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 type 1 military specification single treatment response Style Designator: Straight thru
Media For Which Designed: Hydraulic fluid, petroleum base single response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 type 1 military specification single treatment response Style Designator: Straight thru Shelf Life:
Media For Which Designed: Hydraulic fluid, petroleum base single response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 type 1 military specification single treatment response Style Designator: Straight thru Shelf Life: N/a
Media For Which Designed: Hydraulic fluid, petroleum base single response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 type 1 military specification single treatment response Style Designator: Straight thru Shelf Life: N/a
Media For Which Designed: Hydraulic fluid, petroleum base single response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 type 1 military specification single treatment response Style Designator: Straight thru Shelf Life: N/a Unit Of Measure:
Media For Which Designed: Hydraulic fluid, petroleum base single response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 type 1 military specification single treatment response Style Designator: Straight thru Shelf Life: N/a Unit Of Measure: Demilitarization:
Media For Which Designed: Hydraulic fluid, petroleum base single response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 type 1 military specification single treatment response Style Designator: Straight thru Shelf Life: N/a Unit Of Measure: Demilitarization: No
Media For Which Designed: Hydraulic fluid, petroleum base single response Surface Treatment: Anodize Surface Treatment Specification: Mil-a-8625 type 1 military specification single treatment response Style Designator: Straight thru Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: