

View Online at <https://aerobasegroup.com/nsn/4820-01-503-1549>

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Bolt Hole Quantity:

8 all ends

Valve Operation Method:

Automatic or manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Facility:

Bracket

Valve Size:

4.000 inches

Opening Pressure Setting:

22.0 pounds per square inch

Outside Diameter:

7.6875 inches all ends

Thickness:

1.000 inches all ends

First Connection Face To Centerline Distance:

6.500 inches

Bolt Hole Diameter:

0.6875 inches all ends

Second Connection Face To Centerline Distance:

6.500 inches

Bolt Circle Diameter:

6.5625 inches all ends

Flange Face Design:

Plain all ends

Material:

Nickel alloy flow control device

Material Specification:

Qq-n-288 federal specification single material response seat or astm b-164 assn standard single material response seat

Style Designator:

Err-090

Specification Data:

81349-mil-v-20065 rev c/type a2/ class c government specification and 81349-mil-v-24332 gd. B government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-c-20159 spec.