

View Online at <https://aerobasegroup.com/nsn/4820-01-503-6234>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Pressed-in

Maximum Operating Temp:

400.0 degrees fahrenheit single response

Minimum Operating Temp:

-20.0 degrees fahrenheit

Connection Style:

G54 flared (tube) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Thready Qty Per Inch (tpi):

18 1st end

Maximum Operating Pressure:

200.0 pounds per square inch single response

Thread Size:

0.375 inches 1st end

Opening Pressure Setting:

5.0 pounds per square inch

Product Name:

Relief valve, ebs system; adjustable popoff relief valve

Special Features:

Special cleaning and packaging iaw mil-std-1330d

Material:

Steel comp 316 flow control device

Material Specification:

Uns no s31600 national specification single material response flow control device

Media For Which Designed:

Oxygen, gaseous single response

Style Designator:

Err-090

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-r-83248 spec.