

View Online at <https://aerobasegroup.com/nsn/4820-01-503-6234>

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Poppet

**Disk Loading Method:**

Spring

**Renewable Seat Ring Type:**

Pressed-in

**Maximum Operating Temp:**

400.0 degrees fahrenheit single response

**Minimum Operating Temp:**

-20.0 degrees fahrenheit

**Connection Style:**

G54 flared (tube) 1st end

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube 1st end

**Thready Qty Per Inch (tpi):**

18 1st end

**Maximum Operating Pressure:**

200.0 pounds per square inch single response

**Thread Size:**

0.375 inches 1st end

**Opening Pressure Setting:**

5.0 pounds per square inch

**Product Name:**

Relief valve, ebs system; adjustable popoff relief valve

**Special Features:**

Special cleaning and packaging iaw mil-std-1330d

**Material:**

Steel comp 316 flow control device

**Material Specification:**

Uns no s31600 national specification single material response flow control device

**Media For Which Designed:**

Oxygen, gaseous single response

**Style Designator:**

Err-090

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0

**Mil-std (military Standard):**

Mil-r-83248 spec.