NSN 4820-01-504-1575

Fluid Pressure Regulating Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-504-1575

Body Material:
Nickel copper alloy
Media For Which Designed:
Water, salt
Flow Control Device:
Diaphragm
End Connection Quantity:
2
Maximum Inlet Pressure Rating:
175.0 pounds per square inch
Tempurature Rating:
85.0 degrees fahrenheit
End Connection Specification/std:
Mil-f-20042
Valve Size:
6.000 inches
Product Name:
6 inch class 250 model 30 pressure reducing valve.
6 inch class 250 model 30 pressure reducing valve. Special Features:
· · · · · · · · · · · · · · · · · · ·
Special Features:
Special Features: Stainless steel sprin (25-60 psi range)
Special Features: Stainless steel sprin (25-60 psi range) Shelf Life:
Special Features: Stainless steel sprin (25-60 psi range) Shelf Life: N/a
Special Features: Stainless steel sprin (25-60 psi range) Shelf Life: N/a
Special Features: Stainless steel sprin (25-60 psi range) Shelf Life: N/a Unit Of Measure:
Special Features: Stainless steel sprin (25-60 psi range) Shelf Life: N/a Unit Of Measure: Demilitarization:
Special Features: Stainless steel sprin (25-60 psi range) Shelf Life: N/a Unit Of Measure: Demilitarization: No
Special Features: Stainless steel sprin (25-60 psi range) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:
Special Features: Stainless steel sprin (25-60 psi range) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A21100
Special Features: Stainless steel sprin (25-60 psi range) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A21100 Mil-std (military Standard):
Special Features: Stainless steel sprin (25-60 psi range) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A21100 Mil-std (military Standard):