## NSN 4820-01-504-4387

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Stainless steel stem



View Online at https://aerobasegroup.com/nsn/4820-01-504-4387

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
6 all ends
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Valve Operation Method:
Automatic or manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Facility:
Clamp
Valve Size:
2.0000 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
5.5625 inches all ends
Thickness:
0.4375 inches all ends
First Connection Face To Centerline Distance:
4.000 inches
Bolt Hole Diameter:
0.5625 inches all ends
Second Connection Face To Centerline Distance:
4.000 inches
Bolt Circle Diameter:
4.4375 inches all ends
Flange Face Design:
Plain all ends
Product Name:
2" x 2" dl/b-1 & dl/b-2 series relief valve
Material:
Ota in land at an at any

## NSN 4820-01-504-4387

Safety Relief Valve - Page 2 of 2



Fiig: A046b0