NSN 4820-01-506-8909

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Bonnet Type: Inside spring

Disk

Bolted



View Online at https://aerobasegroup.com/nsn/4820-01-506-8909

Disk Loading Method:
Spring
Bolt Hole Quantity:
6 2nd end
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Valve Operation Method:
Automatic or manual
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Valve Size:
2.500 inches
Adjustable Pressure Range:
+112.0/+128.0 pounds per square inch
Maximum Operating Pressure:
500.0 pounds per square inch single response
Outside Diameter:
6.125 inches 2nd end
Thickness:
0.937 inches 2nd end
First Connection Face To Centerline Distance:
5.500 inches
Bolt Hole Diameter:
0.687 inches 2nd end
Second Connection Face To Centerline Distance:
5.000 inches
Bolt Circle Diameter:
5.000 inches 2nd end
Flange Face Design:
Plain 2nd end
Material:
Nickel alloy flow control device
Material Specification:
Qq-n-288 comp a federal specification single material response seat

NSN 4820-01-506-8909

Safety Relief Valve - Page 2 of 2



Mil-std (military Standard):

Mil-c-20159c spec.