
# NSN 4820-01-508-4080

Safety Relief Valve - Page 1 of 2





Pipe Size Accommodated:

1.000 inches all ends

**Flow Control Device:** 

Disk

### Bonnet Type:

Inside spring

# **Bonnet Attachment Method:**

Bolted

## **Disk Loading Method:**

Spring

#### Valve Discharge Flow Rate:

3.7 cubic feet per minute

**Maximum Operating Temp:** 

128.0 degrees fahrenheit single response

#### Minimum Operating Temp:

28.0 degrees fahrenheit

#### **Connection Style:**

Socket (tube) err-100

#### Valve Operation Method:

Automatic

Connection Type:

Unthreaded internal pipe all ends

# Maximum Operating Pressure:

100.0 pounds per square inch single response

# **Opening Pressure Setting:**

5.00 pounds per square inch

#### **Product Name:**

Pressure relief valve assembly

#### Material:

Stainless steel

## **Material Specification:**

Qq-s-763 federal specification single material response body or astm-a581 or a582 assn standard single material response body or ams

5640 assn standard single material response body

#### Media For Which Designed:

Gas, inert single response

#### Style Designator:

Err-090

#### **Furnished Items And Quantity:**

2 tailpiece and 2 nut

#### Shelf Life:

N/a

#### Unit Of Measure:

# NSN 4820-01-508-4080

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

