NSN 4820-01-508-6251

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-508-6251

Flow Control Device:
Disk
Disk Loading Method:
Weight
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
100.0 degrees fahrenheit single response
End Application:
Valve, sc 1.51
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Facility:
Bracket
Mounting Position:
Horizontal
Valve Size:
1.500 inches
Maximum Operating Pressure:
275.0 pounds per square inch single response
Outside Diameter:
5.000 inches all ends
Face To Face Distance:
6.500 inches
Thickness:
0.563 inches all ends
Bolt Hole Diameter:
0.625 inches all ends
Bolt Circle Diameter:
3.875 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.060 inches all ends
Raised Face Diameter:
2.875 inches all ends
Product Name:
Cast stainless steel swing check valve class 150 b, c r, f

NSN 4820-01-508-6251

Check Valve - Page 2 of 2

Fiig: A530b0



Special Features:
Shock and vibe report number 2-4331-3
Material:
Steel uns j92900
Material Specification:
Astma-351 cf8m assn standard single material response
Style Designator:
Straight through flanged ends
Furnished Items And Quantity:
1 cover and 1 gasket and 1 washer
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No