Check Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-508-6251



Flow Control Device: Disk **Disk Loading Method:** Weight **Bolt Hole Quantity:** 4 all ends **Maximum Operating Temp:** 100.0 degrees fahrenheit single response **End Application:** Valve, sc 1.51 Valve Operation Method: Automatic Flange Shape: Round with holes all ends **Connection Type:** Flange all ends **Mounting Facility:** Bracket **Mounting Position:** Horizontal Valve Size: 1.500 inches Maximum Operating Pressure: 275.0 pounds per square inch single response **Outside Diameter:** 5.000 inches all ends Face To Face Distance: 6.500 inches Thickness: 0.563 inches all ends **Bolt Hole Diameter:** 0.625 inches all ends **Bolt Circle Diameter:** 3.875 inches all ends Flange Face Design: Raised straight all ends **Raised Face Height:** 0.060 inches all ends **Raised Face Diameter:** 2.875 inches all ends **Product Name:** Cast stainless steel swing check valve class 150 b, c r, f

NSN 4820-01-508-6251

Check Valve - Page 2 of 2



Special Features:

Shock and vibe report number 2-4331-3

Material:

Steel uns j92900

Material Specification:

Astma-351 cf8m assn standard single material response

Style Designator:

Straight through flanged ends

Furnished Items And Quantity:

1 cover and 1 gasket and 1 washer

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A530b0