Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-508-7034

	Flow Control Device:
	Disk
	Disk Loading Method:
	Neight
	Bolt Hole Quantity:
	3 all ends
	Maximum Operating Temp:
	100.0 degrees fahrenheit single response
	End Application:
	Valve, sc 6.01
	Valve Operation Method:
-	Automatic
	Flange Shape:
	Round with holes all ends
	Connection Type:
	Flange all ends
	Mounting Facility:
-	Bracket
	Mounting Position:
-	Horizontal
	Valve Size:
	5.000 inches
	Maximum Operating Pressure:
	275.0 pounds per square inch single response
	Outside Diameter:
	11.000 inches all ends
	Face To Face Distance:
	14.000 inches
	Thickness:
	1.000 inches all ends
	Bolt Hole Diameter:
	0.870 inches all ends
	Bolt Circle Diameter:
	9.500 inches all ends
	Flange Face Design:
	Raised straight all ends
	Raised Face Height:
	0.060 inches all ends
	Raised Face Diameter:
	3.500 inches all ends
	Product Name:

Cast stainless steel swing check valve class 150 b, c r, f

# NSN 4820-01-508-7034

Check Valve - Page 2 of 2



### **Special Features:**

Ingalls shipbuilding, project: lpd, req.: 714606trh, item no: 51395.

### Material:

Steel uns j92500 body

# Material Specification:

Astm a-351 cf3 assn standard single material response body

## Style Designator:

Straight through flanged ends

## Furnished Items And Quantity:

1 cover and 1 gasket and 1 washer

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A530b0