

View Online at <https://aerobasegroup.com/nsn/4820-01-508-7057>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Welded

Bolt Hole Quantity:

4 all ends

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Facility:

Bracket

Features Provided:

Bonnet packing

Valve Size:

2.500 inches

Outside Diameter:

7.000 inches all ends

Face To Face Distance:

8.500 inches

Thickness:

0.690 inches all ends

Bolt Hole Diameter:

0.750 inches all ends

Bolt Circle Diameter:

5.000 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.060 inches all ends

Raised Face Diameter:

4.130 inches all ends

Product Name:

Cast stainless steel globe stop check valve, class 150 4, f b, b os&y

Material:

Steel uns j92600 body

Material Specification:

Braided graphite mfr ref single material response packing

Style Designator:

Err-090

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0