NSN 4820-01-510-9886

Calibrated Flow Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-510-9886

Body Material:
Copper alloy
Body Style:
Straight thru
Furnished Items:
Union nut and tailpiece
Media For Which Designed:
Water
First End Connection Type:
Unthreaded internal tube
First End Style Designator:
Socket
First End Outside Diameter Tube Accommodated:
1.000 inches
Second End Relationship With First End:
Identical
Face To Face Distance:
8.594 inches
Flow Control Device:
Diaphragm
Flow Control Device Material:
Rubber, buna-n
End Connection Quantity:
2
Valve Discharge Flow Rate:
14.0 gallons per minute
Regulation Type:
Automatic single stage
Maximum Inlet Pressure Rating:
150.0 pounds per square inch
Tempurature Rating:
160.0 degrees fahrenheit
Valve Size:
1.000 inches
Product Name:
Mesurflo control automatic balancing valve with union end and stainless steel tail pieces.
Special Features:
This valve has bronze union nuts and 304I stainless steel tail pieces.
Test Data Document:
81349-mil-s-901c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

NSN 4820-01-510-9886

Calibrated Flow Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A21100

