NSN 4820-01-510-9891

Calibrated Flow Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-510-9891

Body Material:
Copper alloy
Body Style:
Straight thru
Furnished Items:
Union nut and tailpiece
Media For Which Designed:
Water
First End Connection Type:
Unthreaded internal tube
First End Style Designator:
Socket
First End Outside Diameter Tube Accommodated:
1.000 inches
Second End Relationship With First End:
Identical
Face To Face Distance:
8.594 inches
Flow Control Device:
Diaphragm
Flow Control Device Material:
Rubber, buna-n
End Connection Quantity:
2
Valve Discharge Flow Rate:
17.0 gallons per minute
Regulation Type:
Automatic single stage
Maximum Inlet Pressure Rating:
150.0 pounds per square inch
Tempurature Rating:
160.0 degrees fahrenheit
Valve Size:
1.000 inches
Product Name:
Mesurflo control automatic balancing valve with union end and stainless steel tail pieces.
Special Features:
This valve has bronze union nuts and 304l stainless steel tail pieces.
Test Data Document:
81349-mil-s-901c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

N/a

Shelf Life:

NSN 4820-01-510-9891

Calibrated Flow Valve - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100