## NSN 4820-01-511-0026

Calibrated Flow Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-511-0026

Body Material:
Copper alloy
Body Style:
Straight thru
Furnished Items:
Union nut and tailpiece
Media For Which Designed:
Water
First End Connection Type:
Unthreaded internal tube
First End Style Designator:
Socket
First End Outside Diameter Tube Accommodated:
1.500 inches
Second End Relationship With First End:
Not identical
Second End Connection Type:
Unthreaded internal tube
Second End Style Designator:
Socket
Second End Outside Diameter Tube Accommodated:
1.250 inches
Face To Face Distance:
11.000 inches
Flow Control Device:
Diaphragm
Flow Control Device Material:
Rubber, buna-n
End Connection Quantity:
2
Valve Discharge Flow Rate:
23.0 gallons per minute
Regulation Type:
Automatic single stage
Maximum Inlet Pressure Rating:
150.0 pounds per square inch
Tempurature Rating:
160.0 degrees fahrenheit
Product Name:
1-1/2 x 1-1/4 mesurflo automatic balancing valve with union ends and stainless steel tail pieces
Special Features:
This valve has bronze union nuts and 304I stainless steel tail pieces.

## NSN 4820-01-511-0026

Calibrated Flow Valve - Page 2 of 2



## **Test Data Document:**

81349-mil-s-901c specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A21100